

you can
Canon

iR 2270
iR 2870

Multi Functional Printer

Black and white intelligence
that supports you in the office

The flexible device that
brings new efficiency
to your workgroup.




CHAMPIONS
LEAGUE
OFFICIAL SUPPLIER

Specifications iR 2270 / iR 2870

Type Maximum Original Size	Multi Functional Printer A3
COPY SIZES Cassette Stack Bypass	ASR - A3 A3-A6
RESOLUTION Scanning Copying Printing	600dpi x 600dpi 1200dpi equivalent x 600dpi 2400dpi equivalent x 600dpi 256 Gradients
COPY/PRINT SPEED A4 A3 First copy time Warm-Up Time Multiple Copies/Prints Duplexing	22/28 ppm 14 ppm Less than 4.9 sec 30 sec max (10 sec max from sleep mode) 1 to 999 sheets Standard automatic stackless
PAPER WEIGHT Cassette Stack Bypass Cassette	64 to 80g/m ² 64 to 128g/m ² Universal: ASR to A3
PAPER CAPACITY Standard Optional CPU Memory Hard Disk Drive Interface Power Supply Power Consumption(W) Energy consumption (WdWh) Dimensions (WxDxH) Installation space (WxDxH) Weight	550 sheets x 2 cassettes (1,100 sheets) Multi Stack Bypass: 50 sheets (80g/m ²) 550 sheets x 2 cassettes (1,100 sheets) Side paper deck: 2,500 sheets Max paper capacity: 4,750 sheets 300MHz 256MB (Max: 512MB) 20GB Ethernet (100Base-TX/10Base-T) 230V/5A/50Hz 1.0 kW maximum iR 2270: 16 Whr/h; iR 2870: 19 Whr/h 565 x 700 x 761mm 930 x 1158mm Approx. 70kg
MULTI-POL PRINTER KIT-E1 POL Resolution Memory Hard Disk CPU PS Fonts PCL Fonts Supported OS PCL PS UFR II Mac PPD Interface Network Protocol Pull Scan	PCL5e, PCL6, PostScript3 Emulation and UFR II 2400 equivalent x 600dpi 256MB (up to 512MB) 20GB (Uses Main unit HDD) 300MHz (Uses Main unit CPU) Roman130 Roman80, Bitmap*, Barcode30, OCR2 Windows 98/ME/NTs 0/2000/XP/2003 Windows 98/ME/NTs 0/2000/XP/2003, Mac OSx (10.1.5 or later) PS Windows 2000/XP/2003 Mac OSx or later, Mac OSx (10.1.5 or later) Ethernet (100Base-TX/10Base-T), USB TCP/IP (LPC/Port100/PPS/SSH/FTP), IPX/SPX (NDS, Bindery, AppleTalk) Network Thru Driver (150 to 600dpi/Black & White/Half-tone)
UNIVERSAL SEND KIT-B1 Scan Speed Scan Resolution Destinations Address book File format Single Multi	4.5 ipm: A4: 300/600dpi with DADF 100dpi, 200 x 100dpi, 200dpi, 200 x 400dpi, 300dpi, 400dpi, 600dpi E-Mail/Internet FAX (SMTP), PC (SMB, FTP, NCP), WQEM LDAP, Local (Max 1800) TIFF, PDF TIFF, PDF
DADF-N1 Paper size Paper weight Max. Number of originals Document Scanning speed Copy Scan Dimensions (WxDxH) Weight	A3-ASR Single sided original: A2 to 128g/m ² Double sided original: 50 to 128g/m ² 50 sheets (80g/m ²) A4 22ipm (iR 2270), 28ipm (iR 2870) A4 4.5ipm at 300/600dpi 565 x 538 x 122mm Approx. 8.5kg

CASSETTE FEEDING UNIT-Y2 type Paper Weight Paper Capacity Dimensions (W x D x H) Weight	2 Front-loading adjustable drawers 64 to 80g/m ² 550 sheets (80 g/m ²) x 2 cassettes 585 x 200 x 251.5mm Approx. 23kg
PAPER DECK-Q1 Paper Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight	A4 64 to 105g/m ² 2,500 sheets (80g/m ²) 372 x 591 x 473mm Approx. 29.6 kg
FINISHER-S1 Number of trays Tray capacity Two Trays (Optional) Staple position Staple capacity Weight	One stack tray (inner) & one optional tray One Tray A4-ASR: 1,000 sheets A3: 500 sheets A3-ASR: 300 sheets on each tray Staple position Staple capacity A4: 50 sheets A3: 30 sheets Approx. 12kg
FINISHER-Q3/SADDLE FINISHER-Q4 Number of trays Tray capacity Staple position Staple capacity Saddle Stitch Specifications (Saddle Finisher-Q4 only) Paper size Staple capacity Paper weight Dimensions Weight	2 tray A4-ASR: 1,000 sheets A3: 500 sheets Staple position Staple capacity A4: 50 sheets A3: 30 sheets Saddle Stitch Specifications (Saddle Finisher-Q4 only) Paper size Staple capacity A3, A4R 1 to 15 sheets (60 pages, 64-80g/m ²) 1 to 10 sheets (40 pages, 81-105g/m ²) 64 to 80g/m ² (128g/m ² for Cover) Q3: 536 x 657 x 1035mm Q4: 648 x 657 x 1035mm Q3: 39.6kg Q4: 67.6kg
ACCESSORIES	Platen Cover-H1 DADF-N1 Document Tray-F1 iR3100C pedestal 2 Cassette Feeder Unit-Y2 Paper Deck-Q1 3 Way Unit-A1 Internal Finisher-S1 Additional Finisher Tray-B1 for Finisher S1 Inner 2-way Tray-Q1 Copy Tray-J1 Puncher Unit-Q1/S1 for Finisher-S1 Buffer Pass Unit-E1 External Finisher-Q3/Q4 Puncher Unit-L1/N1 for Finisher-Q3/Q4 Document Tray-F1 Stamp Inc. Cartridge-B1 Staple Cartridge-J1 Staple Cartridge-Q3 Printer Kit-E3 (UFR11) Printer Kit-E2 (UFR11 & PCL) Multi-POL Printer Kit-E1 (UFR11 & PCL & PS) 256MB Expansion RAM-B1 Super G3 FAX Board-Q1 Universal Send Kit-B1 Universal Send PDF Encryption Kit-B1 Universal Send Searchable PDF Kit-A1 USB Application Interface Board-D1 Expansion Bus-B1 iR Security Kit-A2 Card Reader-C1 Card Reader Kit-B1

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ®All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. Final specifications are subject to change without notice. * and ** All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

you can
Canon

Canon Inc.
www.canon.com
Canon Europa N.V.
www.canon-europe.com

Anglo-UK System (0044)770
© Canon Europe NV 2004

Canon (U.K.) Limited
Woodhatch, Reigate
Surrey RH2 8BF
Telephone No: 08000 353535
Facsimile No: 01737 220022
www.canon.co.uk



Conforms to the international
Energy Star program as an EPEAT



POWERED BY



POWERED

